



Serving Canada and United States
Tel: 1-647-880-2111
Email: info@bmeenvironmental.com
www.bmeenvironmental.com

Contaminated Water Treatment Plant Service

BME Environmental provides a revolutionary wastewater cleaning service ahead of current trends with efficient technology equipment that eliminates a wide range of contaminants from water. The



technology has been proven effective on metals, oil production water, effluence, organics - such as bacteria and E-coli, oil and grease, slop oil, silica in water, contaminated mining tailing ponds, and dried contaminated sediments from evaporation ponds – including uranium sediment beds. See test results, below, for a full list of contaminants.

The advanced technology called the “Electro Coagulation” (EC) provides a revolutionizes the treatment and reuse of wastewater.

The EC processes large flows of wastewater making treatment more efficient and cost effective compared to current methods. Other than for pH adjustments and blade cleaning, **no chemicals** are used in the process, resulting in significant reduction in sludge generation. The resulting contaminants are turned into an oxidized non-hazardous state and can be buried anywhere without harm to the ecosystem. This is truly a green operation that gives clean water back to the user.

It is the distinct economical and environmental choice for meeting contaminated water treatment discharge standards and compliance requirements. Volumes can be processed from 50 to 135 GPM (189 to 510 LPM) in a mobile unit to over 10,000 gallons per minute (37,840 Liters Per Minute) at plant operations. The Electro Coagulation technology units have a portable footprint to be on-site where necessary but must be protected by outside elements.



Depending on your requirements, our wastewater treatment services are available on-site or off-site. The Electro Coagulation units are energy efficient eco friendly.

ELECTRO COAGULATION

Water Recovery and Reuse

TEST RESULTS

The following test results were conducted by a qualified independent laboratory or government facility and are specific examples of the patented Electro Coagulation (EC) process. The listed "Removal Rate" indicates the percentage each contaminant was removed from water to an oxidized non-hazardous residue. Therein, the residue can be buried without harm to the ecosystem.

Metals, Ions, Solids, Hardness, and Turbidity

Contaminant	Before mg/l	After mg/l	Removal Rate (%)	Contaminant	Before mg/l	After mg/l	Removal Rate (%)
Aldrin (Pesticide)	0.0630	0.0010	98.40	Mercury	0.7200	<0.0031	98.45
Aluminum	224.0000	0.6900	99.69	Molybdenum	0.3500	0.0290	91.71
Ammonia	49.0000	19.4000	60.41	MP-Xylene	41.6000	0.0570	99.86
Arsenic	0.0760	<0.0022	97.12	MTBE	21.5800	0.0462	99.79
Barium	0.0145	<0.0010	93.10	Nickel	183.0000	0.0700	99.96
Benzene	90.1000	0.3590	99.60	Nitrate	11.7000	2.6000	77.78
BOD5	1050.0000	14.0000	98.67	Nitrite	21.0000	12.0000	42.86
Boron	4.8600	1.4100	70.98	Nitrogen TKN	1118.880	59.0800	94.72
Cadmium	0.1252	<0.0040	96.81	NTU	35.3800	0.3200	99.10
Calcium	1321.0000	21.4000	98.40	O-Xylene	191.0000	0.4160	99.78
Chlorieviphos	5.8700	0.0300	99.50	PCB	0.0007	<0.0001	85.71
Chromium	139.0000	<0.1000	99.92	Petroleum	72.500	<0.200	99.72
Cobalt	0.1238	0.0214	82.71	Phosphate	28.000	0.200	99.28
Copper	0.7984	<0.0020	99.75	Phosphorus	158.750	<10.000	99.93
Cyanide (Free)	723.0000	<0.0200	99.99	Platinum	4.400	0.680	84.55
Cypermethrin	1.3000	0.0700	94.60	Potassium	200.00	110.00	45.00
DDT	0.2610	0.0020	99.20	Propetamphos	80.8700	0.3600	99.60
Diazinon	34.0000	0.2100	99.40	Selenium	68.000	38.000	44.00
Ethyl Benzene	428.0000	0.3720	99.91	Silicon	21.0700	0.1000	99.50
Fluoride	1.1000	0.4150	62.27	Sulfate	104.000	68.000	34.61
Gold	5.7200	1.3800	75.87	Silver	0.0081	0.0006	92.59
Hydrocarbon	72.5000	<0.200	99.72	Tin	0.2130	<0.020	90.61
Iron	68.3400	0.1939	99.72	Tolulene	28480.0	0.2270	99.99
Lead	0.5900	0.0032	99.46	TSS	1560.00	8.0000	99.49
Lindane	0.1430	0.0010	99.30	Vanadium	0.2621	<0.002	99.24
Magnesium	13.1500	0.0444	99.66	Zinc	221.000	0.1400	99.90
Manganese	1.0610	0.0184	98.27				

Organics, Isotopes & Dyes

Bacteria		Before mg/l	After mg/l	Removal Rate %
Bacteria		110,000,000.00 cfu	2,700.00 cfu	99.99
Coliform		318000.00 cfu	<1.00 cfu	99.99
E. coli		>2,419.20 mpn	0.00 mpn	99.99
Enterococcus		83.00 mpn	<10.00 mpn	82.87
Total Coliform		>2,419.20 mpn	0.0000	99.99
Radioisotopes		Before mg/l	After mg/l	Removal Rate %
Americium-241		71.9900 pCi/L	0.5700 pCi/L	99.20
Plutonium-239		29.8500 pCi/L	0.2900 pCi/L	99.00
Radium		1 093.0000pCi/L	0.1000 pCi/L	99.99
Uranium		0.1300 mg/L	0.0002 mg/L	99.83
Dyes		Before NTU	After NTU	Removal Rate %
Ref. 006-691		125.1000	12.1000	90.00
Ref. 006-692		129.4000	2.2000	98.30
Ref. 006-854		68.3000	0.6800	99.00
Ref. 006-851		2340.0000	4.5000	99.80

Synthetic Organofluorine Chemical Compounds (PFAS)

PFAS	Before µg/l	After µg/l	Removal Rate %
PFOA	1.62	<LOD(0.166) *	99.74**
PFOS	0.867	<LOD(0.0981)*	99.44**

* LOD - Limit of Detection (This is the equipment's lowest reading level. The removal rate may be higher than indicated.)

** USEPA New Regulation Limit for PFOA & PFOS is 4 ng/l (ppt) and this is below that level. PFAS is not just removed from the water, it is actually destroyed into a non-hazardous state - it becomes inert after passing through the EC unit.



50 GPM "Electro Coagulation" Unit



600 GPM EC Steel Blade Chamber



Electro Coagulation Plant Setup Operation